

Hardware

Reader for SCU7000/x Universal Control Unit



M400C ACCESS READER WITH BERKER COVER

Access reader with contactless MIFARE/LEGIC reader. The reader has an RS485 interface for connection to an SDC15-V3 Door Controller.

The M400C reader with Berker cover has been developed for Berker switch ranges. Standard: B7, colour: polar white matt. The LEDs display the authorisation status of the read card.

Note: The reader is operated together with an SDC15-V3 Door Controller.

► FEATURES

- Contactless reader technology
- Online operation with SCU7000/x Universal Control Unit and SDC15-V3 Door Controller
- Optical status display via 3 LEDs
- Acoustic feedback via signal transmitter
- Power supply via external power supply for reader, door controller and door strike
- Integrated sabotage contact for connection to universal control unit
- Reading range up to 5 cm

TECHNICAL DATA

Voltage supply	12 V DC external
Max. power input	0,72 W
Max. power consumption	60 mA at 12 V DC
Ambient temperature	-10 to 55 °C
IP protection class	50
Interface	RS485 / 2-wire
Dimensions (H x W x D)	80 x 90 x 45/25 mm
Colour	Polar white matt
Mounting	Flush-mounted and cavity-wall socket

▼ M400C BERKER

MH9778 M400C Berker, MIFARE Classic / DESFire

MH9779 M400C Berker, LEGIC prime / advant


▼ ACCESSORIES AND OPTIONS

MH9222 SDC15-V3 Door Controller

MH8772 Built-in power supply 24 W

MB5384 Decentralised authorisation assignment per reader

Dimensions



Installation example

