

Hardware

EL7000/x Elevator Control Unit Options

CASING-OPTIONS

MIDITEC STEEL WALL CASING WITH LOCK

For EL7000/16/32



Steel wall casing, closed

MIDITEC ADDITIONAL STEEL WALL CASING WITH LOCK (ONLY FOR EL7000/32)

Only for EL7000/32



Additional steel wall casing, closed



Steel wall casing, open, here with UPS



Additional steel wall casing, open

TECHNICAL DATA

Voltage supply	230 V
Ambient temperature	0 °C to 45 °C
Environmental class	II
IP protection class	43
Cable gland	from below
Weight	approx. 7.5 kg (without UPS) approx. 9.7 kg (with UPS)
Dimensions (H x W x D)	30 x 40 x 15.6 cm
Material	steel
Colour	lightgrey (RAL 7035)
Mounting	wall mounting

TECHNICAL DATA

Voltage supply	12 V or 15 V via power supply unit in main steel wall casing
Ambient temperature	0 °C to 45 °C
Environmental class	II
IP protection class	43
Cable gland	from below
Weight	approx. 5,4 kg
Dimensions (H x W x D)	30 x 30 x 15.6 cm
Material	steel
Colour	lightgrey (RAL 7035)
Mounting	wall mounting